

Foot Mounted (B3) Construction

FRAME SIZE	A	B	C	H	K	U	L	LC	AA	AB	BB	AC	HA	HD	AD	D DA	E EA	F FA	GA GC	G GB	TOL ON D.DA	TOL ON F.FA	TOL ON H
63	100	80	40	63	7	M4	210	238	35	125	106	115	10	158	95	11	23	4	12.5	8.5	+0.008	+0.0 -.030 (h9)	+0.0 -.5
71	112	90	45	71	7	M5	240	275	35	140	112	140	10	176	105	14	30	5	16	11	-0.003 (J6)		
80	125	100	50	80	10	M6	280	322	38	160	130	162	13	161	128	19	40	6	21.5	15.5			
90S	140	100	56	90	10	M8	316	369	37	175	132	173	14	177	135	24	50	8	27	20	+0.009	+0.0 -.036 (h9)	
90L	140	125	56	90	10	M8	331	394	37	175	157	173	14	177	135	24	50	8	27	20	-0.004 (J6)		
100L	160	140	63	100	12	M10	372	437	42	200	170	195	14	245	165	28	60	8	31	24			
112M	190	140	70	112	12	M10	390	464	50	225	175	226	14	285	178	28	60	8	31	24		+0.008 -.002 (K6)	
132S	216	140	89	132	12	M12	454	540	55	258	176	260	18	320	198	38	80	10	41	33			
132M	216	178	89	132	12	M12	484	578	55	258	214	260	18	320	198	38	80	10	41	33			
160M	254	210	108	160	15	M16	585	700	72	320	260	310	25	390	240	42	110	12	45	37	+0.008 -.002 (K6)	+0.0 -.043 (h9)	
160L	254	254	108	160	15	M16	625	744	72	320	304	310	25	390	240	42	110	12	45	37			
180M	279	241	121	180	15	M16	680	795	80	360	300	360	25	445	260	48	110	14	51.5	42.5			
180L	279	279	121	180	15	M16	680	795	80	360	338	360	25	445	260	48	110	14	51.5	42.5			
200L	318	305	133	200	19	M20	750	865	85	400	370	390	30	465	295	55	110	16	59	49		+0.030 -.011 (m6)	
225S*	356	286	149	225	19	M20	800	905	85	440	370	390	30	490	295	55	110	16	59	49			
225S*	356	286	149	225	19	M20	830	965	85	440	370	390	30	490	295	60	140	18	64	53			
225M	356	311	149	225	19	M20	800	905	85	440	370	390	30	490	295	55	110	16	59	49			
225M**	356	311	149	225	19	M20	830	965	85	440	370	390	30	490	295	60	140	18	64	53			